

DRUM MACHINE

D-1000

- Applicable for both indoor and outdoor of $\Phi 32\sim 100\text{mm}$ (1 1/4"-4") in lavatories, bathrooms and kitchens. With $\Phi 12.5\text{mm}$ (1/2") Inner-core cable.
- Entirely sealed structure, flexible soft shafts are put in drum, to ensure cleaner and more convenient use.
- Drum spin at 250rpm, cable feeding speed 5m/min.
- Input power: 390W.
- Rated voltage: 220V; 110V optional, Frequencies of 50HZ;
- 60HZ optional.

The drum can be adjusted to fit different working position



Pressure Knob

Auto-feed device

Adjust spanner



CE NO:2.2011 GQ-75

Inner-core cable High Intensity Anti-twisting Anti-kinking
High quality steel wire coiled around the steel wire rope tightly and special treated, the inner-core cable can meet the requirement of every heavy duty job.

Basic Equipments

Catalog No.	Type.	Description	Weight
2.3018A	D-1000A	Main machine	37.80 Kg.
		R-8-1 $\Phi 12.7\text{mm} \times 15\text{m}$ (1/2" \times 50') inner-core cable	10.50 Kg.
		ZHa-5 $\Phi 16\text{mm}$ drills 4 pieces	0.19 Kg.
		F-7-d Auto-Feed device	0.54 Kg.
		F-3-a $\Phi 4$ Key	0.03 Kg.
2.3018B	D-1000A	Main machine	37.80 Kg.
		R-8-2 $\Phi 12.7\text{mm} \times 15\text{m}$ (1/2" \times 50') inner-core cable	16.10 Kg.
		ZHa-5 $\Phi 16\text{mm}$ drills 4 pieces	0.19 Kg.
		F-7-d Auto-Feed device	0.54 Kg.
		F-3-a $\Phi 4$ Key	0.03 Kg.

ZHa-6 $\Phi 16$ mm drills



NO:2.0225 T-2-e
Bulb Auger



NO:2.0225 T-2-e
Retrieving Auger



NO:2.0275 T-7-e
Grease Cutter



NO:2.0285 T-8-e
Sawtooth Cutter

Accessories



NO:2.0331 F-3-a
 $\Phi 4$ Key



NO:2.0374 F-7-d
Protection Tube