

SECTIONAL MACHINE



Basic Equipments

Catalog No.	Type.	Description	Weight
2.2011	GQ-75	2.2001 Main machine	112.20 Kg.
		RH1-1 Φ 16mm soft shafts	9.26 Kg.
		ZHa-1 Φ 16mm drills 8 pieces	0.42 Kg.
		F-3-a Φ 4 key	0.03 Kg.
		F-2-a Φ 8mm x 5m soft shaft combination	2.38 Kg.
		F-5-a Protection gloves	0.25 Kg.
		F-6-a Accessory barrel	2.00 Kg.

SECTIONAL MACHINE



GQ-75

- Applicable for all kinds of indoor pipes of Φ 20-100mm (3/4"-4").
- Lightweight, strong, convenient flexible in operation, using soft shafts of Φ 8mm (5/16") and Φ 16mm can be used.
- Soft shaft of Φ 8mm (5/16") are used to clean pipes of Φ 20-75mm in diameter, especially applicable to complex pipes of small diameters like traps.
- Flexible soft shafts of Φ 16mm (5/8") are used to clean small complex.
- Using sectional helical flexible shafts of Φ 16mm (5/8"), pipes of Φ 32-100mm (1 1/4"-4") in diameter can be cleaned, the soft shafts can be lengthened at will.
- Press the clutch, the rotating speed is up to 400 rpm, and the soft shaft stops when the handle is released.
- Input Power: 390W.
- Rated Voltage: 220V, 110V optional, frequency 50Hz, 60Hz optional.

RH1-1 Φ 16 mm Soft Drills

 NO:2.2111 RH1-1 Φ 16mm Soft shaft		2.0131 R-3-1	1 piece Φ 16mmx2.3m flexible soft shafts
		2.0141 R-4-1	7 pieces Φ 16mmx2.3m soft shafts
		2.0316 F-1-f	Φ 430 soft shaft holder



ZHa-6 Φ 16 mm drills

			
NO:2.0211 T-1-a Straight Auger	NO:2.0211 T-2-a Bulb Auger	NO:2.0231 T-3-a Flexible Bulb Auger	NO:2.0251 T-5-a Retrieving Auger
			
NO:2.0261 T-6-a 4-Blade Cutter	NO:2.0271 T-7-a Grease Cutter	NO:2.0281 T-8-a Sawtooth Cutter	NO:2.0291 T-9-a "C" cutter

Accessories

		
NO:2.0316 F-6-a Accessory Barrel	NO:2.0321 F-2-a Φ 8mm*5m soft shaft combination	NO:2.0351 F-3-a Φ 4 Key
		Optional Purchase Part
NO:2.0351 F-5-a Protection gloves	NO:2.0291 F-7-a Optional 1.8 m Protection tube	